

Technical data

HC 50i P



Compactors Series HC CompactLine

Compactor with padfoot drum

H288

HIGHLIGHTS

- > High climbing ability
- > Excellent view of the machine and the construction site
- > Compact dimensions
- > Simple, intuitive and language-neutral operation
- > 3-point articulation for outstanding traction and off-road mobility

TECHNICAL DATA HC 50i P (H288)

Weights

Operating weight with cab	kg	5410
Operating weight with ROPS	kg	5175
Empty weight without cab, without ROPS	kg	4910
Max. operating weight	kg	5870
Axle load, front/rear	kg	2945/2465
French classification, value/class		25,53/VPM2
Wheel load per tyre, rear	kg	1232,5

Machine dimensions

Total length	mm	4040
Total height with cab	mm	2838
Total height with ROPS	mm	2835
Height loading, min.	mm	2835
Centre distance	mm	2169
Total width with cab	mm	2018
Maximum working width	mm	1370
Ground clearance, centre	mm	277
Kerb clearance, left/right	mm	330/330
Turning radius, inside	mm	3375
Slope angle, front/rear	°	43/36

Drum dimensions

Drum width, front	mm	1370
Drum diameter, front	mm	1155
Drum thickness, front	mm	15
Drum type, front		Padfoot
Height of the padfeet	mm	82,5
Padfeet, quantity		60

Tyre dimensions

Tyre size, rear		TR 12.4-24 8 PR
Width over tyres, rear	mm	1500
Number of tyres, rear		2

Diesel engine

Manufacturer		DEUTZ
Model		TD 2.9 L4
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		54,0/73,4/2200
Power SAE J1349, kW/HP/rpm		54,0/72,4/2200
Exhaust emission standard		EU Stage IIIB / EPA Tier 4
Exhaust gas after-treatment		DOC

Travel drive

Speed, working gear	km/h	0-6,0
Speed, transport gear	km/h	0-11,8
Gradeability, with/without vibration	%	54/60

Vibration

Vibration frequency, front	Hz	30
Amplitude, front	mm	1,51
Centrifugal force, front	kN	69

Steering

Swing angle +/-	°	10
Steering, type		Articulated steering

Tank capacity/filling capacity

Fuel tank, capacity	L	123
---------------------	---	-----

Sound level

Sound power level L(WA), guaranteed	db(A)	105
Sound power level L(WA), representative measurement	db(A)	104

EQUIPMENT

12 V sockets (double) | Two large exterior rear-view mirrors | 3-point articulation | Storage compartment behind the driver's seat | Storage compartment below the driver's seat | Storage compartments | Anti-slip control | Dashboard with displays, indicator lights and switches | Fixture for cool box | ECO mode | Spring-mounted driver's seat with armrest and seat belt | Cup holder | Large slope angle at front and rear | Hose protection on the front vehicle | Vibration-isolated driver's platform | Maintenance points, central on one machine side

OPTIONAL EQUIPMENT

ROPS cab with heating and air-conditioning system (FOPS, level I) | Seat belt monitoring device | Bluetooth interface for Smart Doc | Protective roof | Dozer blade | Speedometer | Automatic engine stop | Camera system | Back-up alarm | JDLINK | Working spotlights | Battery isolation switch