

Technical data

HD 10 VV



Tandem rollers Series HD CompactLine

Tandem roller with two vibrating roller drums

H230

HIGHLIGHTS

- > Easy transport, simple loading
- > Simple, intuitive and language-neutral operation
- > Compact dimensions
- > Excellent view of the drum edges, the machine and the construction site surroundings
- > Ergonomic driver platform

TECHNICAL DATA HD 10 VV (H230)

Weights

Operating weight with ROPS	kg	2475
Max. operating weight	kg	3190
Static linear load, front/rear	kg/cm	12,1/12,7
French classification, value/class		12,7/PV3

Machine dimensions

Total length	mm	2530
Total height with ROPS	mm	2475
Height loading, min.	mm	1752
Centre distance	mm	1700
Total width	mm	1110
Maximum working width	mm	1050
Ground clearance, centre	mm	280
Kerb clearance, left/right	mm	570/570
Turning radius, inside	mm	2470

Drum dimensions

Drum width, front/rear	mm	1000/1000
Drum diameter, front/rear	mm	720/720
Drum thickness, front/rear	mm	15/15
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Track offset, left/right	mm	0/50

Diesel engine

Manufacturer		Kubota
Model		D1703-M-DI-E4B
Cylinders, quantity		3
Power ISO 14396, kW/PS/rpm		18,2/24,8/2200
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		-

Travel drive

Speed, infinitely variable	km/h	10,2
Gradeability, with/without vibration	%	30/40

Vibration

Vibration frequency, front, I/II	Hz	65/51
Vibration frequency, rear, I/II	Hz	65/51
Amplitude, front, I/II	mm	0,45/0,45
Amplitude, rear, I/II	mm	0,45/0,45
Centrifugal force, front, I/II	kN	33/20
Centrifugal force, rear, I/II	kN	33/20

Steering

Swing angle +/-	°	8
Steering, type		Articulated steering

Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

Tank capacity/filling capacity

Fuel tank, capacity	L	42
Water tank, capacity	L	180

Sound level

Sound power level L(WA),	db(A)	106
--------------------------	-------	-----

Sound level

guaranteed		
Sound power level L(WA), representative measurement	db(A)	104

EQUIPMENT

12 V power socket | 3-point articulation | Dashboard with displays, indicator lights and switches | Dashboard cover, lockable and weather-resistant | Pressure water sprinkling system | Driver's platform with entry from both sides | Drive lever, left and right | Mechanical battery isolation switch | Vibration-isolated driver's platform | Track offset, mechanical | Automatic vibration system | Water filter system (3-fold) | Central lifting bracket | Central water outlet

OPTIONAL EQUIPMENT

Plastic scraper, folding | ROPS, foldable | Plastic tarpaulin | Edge pressing and cutting equipment | Back-up alarm | Working spotlights | Battery isolation switch with cable control actuation | V-belt protection