

Technical data

# HD+ 140i VV-HF



**Tandem rollers Series HD+**

Tandem roller with two vibrating roller drums

**H304**

**HIGHLIGHTS**

- > Operating concept Easy Drive
- > 3-point articulation for even weight distribution and excellent directional stability
- > Innovative cabin concept for optimal visibility and high comfort
- > Seat-operating unit can be moved and rotated
- > Digital ready

**TECHNICAL DATA HD+ 140i VV-HF (H304)**

**Weights**

Operating weight with cab	kg lbs	13740 30,297
Operating weight with ROPS	kg lbs	13510 29,790
Empty weight without cab, without ROPS	kg lbs	12425 27,397
Max. operating weight	kg lbs	14770 32,568
Axle load, front/rear	kg lbs	6880/6860 15,170/15,126
Static linear load, front/rear	kg/cm lbs/in	32,15/32,06 180.0/179.5
French classification, value/class		25,03/VT1

**Machine dimensions**

Total length	mm in	5300 208.7
Total height with cab	mm in	2980 117.3
Total height with ROPS	mm in	3030 119.3
Height loading, min.	mm in	2140 84.3
Center distance	mm in	3900 153.5
Total width with cab	mm in	2260 89.0
Maximum working width	mm in	2310 90.9
Ground clearance, center	mm in	340 13.4
Curb clearance, left/right	mm in	900/900 35.4/35.4
Turning radius, inside	mm in	6200 244.1

**Drum dimensions**

Drum width, front/rear	mm in	2140/2140 84.3/84.3
Drum diameter, front/rear	mm in	1400/1400 55.1/55.1
Drum thickness, front/rear	mm in	19/19 0.7/0.7
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Track offset, left/right	mm in	170 6.7

**Diesel engine**

Manufacturer		DEUTZ
Model		TCD 4.1 L4
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		115,0/156,4/2300
Power SAE J1349, kW/HP/rpm		115,0/154,1/2300
Exhaust emission standard		EU Stage V / EPA Tier 4

**Diesel engine**

Exhaust gas after-treatment		DOC-DPF-SCR
-----------------------------	--	-------------

**Travel drive**

Speed, infinitely variable	km/h mph	0-10,5 0.0-6.5
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	35/39

**Vibration**

Vibration frequency, front, level I/II	Hz vpm	45/67 2,700/4,020
Vibration frequency, rear, level I/II	Hz vpm	45/67 2,700/4,020
Amplitude, front, level I/II	mm in	0,65/0,20 .026/.008
Amplitude, rear, level I/II	mm in	0,65/0,20 .026/.008
Centrifugal force, front, level I/II	kN lbs	160/105 36,000/23,625
Centrifugal force, rear, level I/II	kN lbs	160/105 36,000/23,625

**Steering**

Pendulum angle +/-	°	10
Steering, type		Articulated steering

**Water-sprinkling system**

Water sprinkling, type		Pressure
------------------------	--	----------

**Tank capacity/filling capacity**

Fuel tank, capacity	L Gal	260 68.7
AdBlue/SCR reducing agent tank, capacity	L Gal	20 5.3
Water tank, capacity	L Gal	1145 302.5

**Sound level**

Sound power level L(WA), representative measurement	db(A)	109
---	-------	-----

**EQUIPMENT**

Scrapers foldable | Pressure water sprinkling system | ECO mode | Speed preselect | Track offset, hydraulic | Water filter system (3-fold) | Central water outlet

**OPTIONAL EQUIPMENT**

Heating and air-conditioning system | Tachograph | Bluetooth interface for Smart Doc | Smart Compact | Weather station | Edge pressing and cutting equipment | HAMM Compaction Meter (HCM) | HAMM Temperature Meter (HTM) | Camera system | JDLINK | Working spotlights | Drum edge lighting | Coming Home function